

Japanese THK double-slide lead rail



Print head lifting system



The resolution of platform and y girder+ 0.2mm



Four separate color ink pressure system



Precise feeding system



Print head protection system



Pre-heat, bed-heat and large area front-heat



K3208A:KONICA-512/14PL 8 HEAD

resolution	Print mode	Speed(m ² /h)	Media type
360×1080	3 pass	50	Banner
	6 pass	23	Banner,PVC
360×1440	4 pass	40	Banner,PVC
	8 pass	18	Banner,PVC
720×720	4 pass	20	Banner,PVC

K3208B:KONICA-512/42PL, 8 HEAD

This type adopts 8 Konica 512 head and the speed is equal to 32 XAAR 128/40pl.

resolution	Print mode	Speed(m ² /h)	Media type
180×720	2 pass	75	Banner
240×720	2 pass	60	Banner
240×1080	3 pass	40	Banner
240×720	4 pass	28	Banner,PVC
360×720	6 pass	22	Banner,PVC

K3208C:KONICA-256/14PL 8 HEAD

This type adopts Konica 256/14pl 8 head, the speed and resolution that under the 6/8/12 pass mode are equal to Konica 512/14pl 8 head. This type holds the cost advantage on equipment investment and head which is suit to the customers that requires high resolution.

resolution	Print mode	Speed(m ² /h)	Media type
360×720	4 pass	40	Banner
360×1080	6 pass	23	Banner,PVC
360×1440	8 pass	18	Banner,PVC
720×540	3 pass	26	Banner
720×720	4 pass	20	Banner,PVC

SPECIFICATION

Product types:K3208-A K3208-B K3208-C

Printing technology: Piezo printing

Print head quantity/type:8, 14PL(K3208-A) KONICA-512,8, 42PL(K3208-B) KONICA-512,8, 14PL KONICA-256(K3208-C)

Media transmission: roll to roll

Printing port: USB

Max printing width:3200mm

Printing resolution:360dpi / 720dpi/1080dpi / 1440dpi

RIP software: PHOTOPRINT□MAINTOP□ULTRAPRINT(rip and print simultaneously or print after rip)

Heating system: pre-heater, front-heater, and bed-heater.

Cleaning system: Air pressure and suction cleaning

Frame structure: steady steel structure is used on the machine body, and the combination of aluminum and steel on the girder.

Colors :C, M, Y, K orC, M, Y, K, LC, Lm solvent ink

Main power:220V AC

System :220V±10%, <4A, 50/60HZ

Heating :220±10%, <16A, 50/60HZ

Operation environment :temperature :20°C□30°C, humidity:40%□70%RH

Media type: banner□adhesive vinyl□PVC self-adhesive, backlit film, flex media within 5mm thickness.

Dimension :□W×H×L□ 750×1278×4500mm

Net weight /Gross weight:400kg/500kg