

| 型号 Model | FS3316 | |
|---------------------------------------------------|-------------------------------------------------------------------------------------------|--------------------------------------|
| 喷头技术 Print Technique | Xepr 128/128Plus 16个打印头(可选12/8个) Xepr 128/128Plus 16 Print-heads (Optional 12/8 heads) | |
| 打印精度 Printing resolution | 360dpi/720dpi | |
| 最大介质宽度 Max Media Width | 3300mm | |
| 最大打印宽度 Max Printing Width | 3250mm | |
| 最小介质尺寸 Min Printing Size | A4 或 210mm长 A4 or 210mm | |
| | 2 pass (360dpi) | 62m ² /h |
| 速度 (720dpi打印模式) Output (720dpi printing model) | 3 pass (540dpi) | 43m ² /h |
| | 4 pass (720dpi) | 31m ² /h |
| 墨水类型 Ink Type | 溶剂型: C, M, Y, K Solvent ink: C, M, Y, K | |
| 打印软件 Printing Driver | Photoprint 6 / Maintop | |
| 操作平台 Operation Platforms | Window2000, XP Multi-operation platforms (Window2000, XP) | |
| 介质类型 Media Type | 灯箱布, 车身贴, 网格布, 旗帜布等 Flex, vinyl, window film, polyester, etc. | |
| 介质输送 Media Processing | 自动放布, 自动收卷 Auto feeding and take-up system | |
| 介质加热 Pre-heater & Dry System | 自动加热控制, 可调 Auto heating after electrifying, the tiptop temperature is about 40°C | |
| 安全 Safety System | 内部安全急停设计 Inside safety lock with auto shutting down function | |
| 净重尺寸 Net Weight | L 4500mm×W 750mm×H 1300mm / 350kg | |
| 毛重尺寸 Gross weight | L 5000mm×W 800mm×H 1500mm / 350kg | |
| 电源电压 Input Voltage | AC 100 - 240 V, 50HZ/60HZ | |
| 电源消耗 (AC 220V 时) Power (AC 220V applied) | Control: ≤3A | Heating: ≤5A Feeding, Fan: ≤5A |
| 工作环境 Working Environment | 温度: 20C - 28C Temperature: 20C - 28C | 湿度: 40% - 70% Humidity: 40% - 70% |